

MG8RL / MG10RL

NEW



Robust Power Performance

- 100% full power backup output, delivering stable performance even at temperatures above 45 °C
- Whole-home backup with 63 A bypass switch



Robust Backup Power

- 4 ms Seamless Switch*
- 10 seconds of 200% backup peak power capability



Robust Solar Generation

- Industry-leading Max. 20 A PV input per string
- Wider MPPT voltage range



Robust Safety Features

- Dual-system pressure relief structure



Robust Control Interface

- 4.3-inch large LCD touchscreen
- Multi-functional interface for Generator, Smart load control or Sungrow string inverter



Type designation	MG8RL	MG10RL
Input (DC)		
Recommended max. PV input power	16000 Wp	20000 Wp
Max. usable PV input power	12800 Wp	16000 Wp
Max. PV input voltage	500 V	
Min. PV input voltage / Startup input voltage	40 V / 50 V	
Rated PV input voltage	360 V	
MPPT operating voltage range**	40 V – 425 V	
No. of independent MPP trackers	3	
No. of PV strings per MPPT	1 / 1 / 1	
Max. PV input current	60 A (20 A / 20 A / 20 A)	
Max. DC short-circuit current	75 A (25 A / 25 A / 25 A)	
Max. current for DC connector	25 A	
Battery data		
Battery type	Li-ion battery	
Battery voltage range	40 V – 60 V	
Max. charge / discharge current***	190 A / 190 A	220 A / 220 A
Max. charge / discharge power	8000 W / 8000 W	10000 W / 10000 W
Input / Output (AC)		
Max. AC power from grid	13860 W	
Rated AC output power	8000 W	10000 W
Max. AC output apparent power	8000 VA	10000 VA
Max. AC output current	36.4 A	45.5 A
Rated AC voltage	220 V / 230 V / 240 V	
AC voltage range	154 V – 276 V	
Rated grid frequency	50 Hz / 60 Hz	
Grid frequency range	45 Hz – 55 Hz / 55 Hz – 65 Hz	
Harmonic (THD)	< 3% (of rated power)	
Power factor at rated power / Adjustable power factor	> 0.99 at default value at rated power / 0.8 leading to 0.8 lagging	
Feed-in phases / Connection phases	1 / 1	
Backup Data (on grid mode)		
Max. output power for backup load ****	13860 W	
Max. output current for backup load	63 A	
Backup Data (off-grid mode)		
Rated voltage	220 V / 230 V / 240 V	
Rated frequency	50 Hz / 60 Hz	
THDV (@ Linear load)	< 2%	
Backup switch time	≤ 4 ms	
Rated output power	8000 W	10000 W
Max. output power for backup load	8800 W	11000 W
Peak output power	2 times of rated power, 10 s	
Efficiency		
Max. efficiency / European efficiency	97.6% / 96.7%	
Protection & Function		
Grid monitoring	Yes	
DC reverse polarity protection	Yes	
AC short-circuit protection	Yes	
Leakage current protection	Yes	
DC switch (solar)	Yes	
Surge protection	DC Type II / AC Type II	
PID Zero	Yes	
Micro-inverter compatibility *****	Optional	
General Data		
Topology (Inverter)	Non-isolated	
Topology (Battery BDC)	Isolated	
Degree of protection	IP65	
Dimensions (W * H * D)	552 mm * 448 mm * 250 mm	
Weight	≤ 25 kg	
Mounting method	Wall-mounting bracket	
Operating ambient temperature range	-25 °C to 60 °C	
Allowable relative humidity range	0% – 95%	
Cooling method	Fan cooling	
Max. operating altitude	2000 m	
Noise (typical)	≤ 45 dB (A)	
Display	LCD digital touchable display & LED indicator	
Communication	CAN, RS485, Ethernet (optional), WLAN (optional)	
DI / DO	DI * 1 / DO * 1	
DC connection type	MC4 compatible (Max. 6 mm²)	
Battery connection type	OT terminal (35 mm² – 95 mm²)	
AC connection type	OT terminal (Max. 16 mm²)	
Scalability*****	8 in parallel	
Grid compliance	IEC 62109-1/-2, IEC/EN 61000-6-1/-3, IEC 62116, IEC 61727, NRS 097-2-1, MEA, PEA, DEWA	

* Available in typical conditions

** Please refer to the user manual for the full load MPPT voltage range

*** The system's charging and discharging capability is also limited by the battery's charging and discharging performance

**** Please refer to the user manual and modify the settings based on actual load power

*****For micro-inverter compatibility, it is only available for the grid-connection port of the inverter

*****If the number of inverters in parallel exceeds 4, please consult SUNGROW

MBL050 / MBL120 / MBL160



Long lifespan

- Up to 8,000-cycle lifespan ensures reliable, long-term use



Safety

- High-safety LFP battery
- Supports up to 5 types of safety detection



Flexibility

- Supports parallel connection of 2 to 20 modules, scalable up to 320 kWh



Easy Installation

- Touchscreen for easy operation
- Equipped with wheels for effortless transport¹⁾



Technical properties	MBL050	MBL120	MBL160
System Data			
Battery type	LiFePO4		
Nominal energy	5.12 kWh	11.8 kWh	16.08 kWh
Battery cycles ²⁾	6000	6000	8000
Nominal voltage	51.2 V		
Voltage range	44.8 V – 57.6 V		
Nominal charging / discharging current	50 A / 50 A	115 A / 115 A	157 A / 157 A
Max. charging / discharging current	100 A / 100 A	230 A / 230 A	200 A / 200 A
Peak charging (1s) / discharging current (3s)	110 A / 150 A	250 A / 300 A	210 A / 300 A
Min. discharging current	2 A		
Communication			
Display	LCD touchscreen		
Language	Chinese, English, Arabic, French		
Display Parameters	SOC, Pack voltage, Pack current, Charging / Discharging status		
Communication interface	CAN / RS485		
Protection			
Over / under voltage protection	Yes		
Over current protection	Yes		
Over / under temperature protection	Yes		
DC breaker	Yes		
General Data			
Dimensions (W * H * D)	494 * 513 * 155 mm	432 * 715 * 243 mm	432 * 855 * 243 mm
Weight	47.5 kg	86.5 kg	114.2 kg
Degree of protection	IP20		
Mounting method ¹⁾	Floor-mounted (Build-in casters) or Wall-mounted		
Installation location	Indoor		
Operating ambient temperature range	Charge: 0 to 55 °C (32 °F to 131 °F) Discharge: -20 to 55 °C (-4 °F to 131 °F)		
Allowable relative humidity range	5% to 95% (non-condensing)		
Storage condition	6 months @ 25 °C; 3 months @ 35 °C; 1 month @ 45 °C		
Max. operating altitude	2000 m		
Cooling method	Natural convection		
Max. parallel units	20		
Certification	CE, IEC 62619, IEC 62477, UN 38.3, MSDS, RoHS		
Compatible inverters	MG5 / 6 / 8 / 10 / 12RL		

¹⁾ Wall mounting only for MBL050. MBL120 and MBL160 require additional wall mounting accessories.

²⁾ Life cycle test conditions: 90% DOD, 0.5C charge & discharge at 25°C.